

SUBJECT INDEX

-A-

- Adaptive forward error correction, 7-79, 7-117
- Advanced Communications Technology Satellite (ACTS), 7-18, 7-24, 7-78, **7-117**
- Amplitude dispersion data, 5-39
- Amplitude fluctuations, 6-76, 6-101, 6-126, 6-129
- Angle diversity (see: Orbit diversity)
- Angle-of-arrival
 - definitions, 6-94
 - fluctuations, 6-103
- Antenna
 - aperture effects, 6-75
 - axial ratio, 4-15
 - gain equation, 7-52
 - non-ideal performance, 4-15
 - wave interaction, 4-8
- ATDRSS, 7-35
- ATS-5** satellite, 5-21
- ATS-6** satellite, 4-40, 5-3, 5-4, 5-22
- Attenuation
 - clear-air, see gaseous
 - cloud , 1-4, 7-63
 - co-polarized (CPA), 4-33
 - differential, 4-29
 - dust , 6-73, 7-63
 - fog, 1-4, 6-71
 - gaseous, 6-7, 7-63
 - rain, 1-6, 3-1
 - sand, 6-73
 - specific rain, 2-7, 2-11, 4-25
- Attenuation, rate of change, 6-56
- Attenuation statistics
 - 11.5 - 11.7 GHz, 5-8
 - 15 - 16 GHz, 5-18
 - 19 - 20 GHz, 5-22
 - 28 - 35 GHz, 5-22
 - analytic estimates, 6-20
 - diurnal distribution, 5-29
 - elevation angle scaling, 5-15, 6-48
 - extension, 6-44
 - extension example, 6-48
 - fade duration distribution, 5-35
 - format, 5-5
 - frequency scaling, 5-25, 6-47
 - histograms, 5-27, 5-31, 5-34
 - joint attenuation - depolarization, 5-36, 7-60

- monthly distribution, 5-28
- prediction**
 - from limited rain rate and attenuation statistics, 6-43
 - from rain rate statistics, 6-41
 - using CCIR model, 6-32
 - using Global model, 6-23
- procedures for calculating, 6-20
- worst month, 6-59
- Availability, 7-8, 7-73
- Axial ratio 4-7, 4-16

-B-

- Bandwidth coherence
 - ionospheric effects, 6-129
 - tropospheric effects, 6-126
- Beacons (see: Propagation beacons)
- Bit error rate, 7-9
- BS satellite, 5-3, 5-4

-C-

- Canting angle, 4-29, 4-37
- CCIR** (International Radio Consultative Committee), 5-1, 7-9
 - rain attenuation model, 3-2, 3-44, 6-32, 6-37
 - sample calculation, 6-35
 - rain depolarization model, 4-36
- Clear-air attenuation, 6-7, 7-63
- Clear-air fluctuations, 6-75
- Climatological** Data Reports, 2-16
- Clouds
 - attenuation statistics, 6-67
 - measured attenuation, 6-64
 - water content, 6-64
- Coherence bandwidth
 - amplitude variations, 6-126
 - experimental results, 6-127
 - ionospheric effects, 6-129
 - phase variations, 6-129
 - tropospheric effects, 6-126
- COMSTAR** satellite, 4-40, 5-4, 5-22, 5-28, 5-29, 5-36, 5-39
- Copolarized** attenuation (CPA), 4-33, 5-33
- Copolarized** wave, 4-2, 4-15
- Crosspolarization, 1-6
 - discrimination (**XPD**), 4-2, 4-13, 4-32, 5-33
 - isolation (**XPI**), 4-2
 - signal phase, 4-43
- Crosspolarized wave, 4-2
- CS satellite, 5-3, 5-4, 5-24
- CTS satellite, 4-40, 5-4, 5-8
- Cumulative statistics, 5-8
 - definition, 6-19
 - format, 5-5
- Cyclonic** storm, 2-2

-D-

Data rate reduction, 7-80, 7-120

Debris rainfall, 3-42

Defense Communications Agency (DCA) , 7-9

Delay

 ionospheric, 6-5

 tropospheric, 6-5

Department of Commerce (DOC) , 6-2

Depolarization

 analysis, 7-58

 data, 4-39, 5-33, 6-105

 11.7 GHz

 19 GHz, 5-36

 28 GHz, 5-36

 joint depolarization - attenuation, 5-36, 7-60

 phase variations, 4-43

 definition of terms, 4-1

 hail and snow, 4-6, 6-120

 hydrometer, 4-4, 6-104

 ice crystal, 4-5, 4-47

 elevation angle and frequency dependence, 6-113

 ice crystal parameters, 4-47, 6-115

 measurements, 6-115

 model, 4-49, 6-119

 mathematical formulations, 4-7, 6-105

multipath, 4-4, 6-120

 due to refractivity gradients

 prediction, 6-104

 rain, 1-6, 4-4, 4-5, 4-23, 6-106

 CCIR approximation, 1-7, 4-36, 5-33, 6-106

 elevation angle dependence, 4-45, 6-113

 experimental results, 4-39, 5-33, 6-107

 frequency dependence, scaling, 4-45, 6-111

 phase variations, 4-43, 6-115

 prediction of statistics, 6-19

 rate of change, 4-44

 statistical characteristics, 4-39

 theory, 4-23

 versus rain attenuation, 4-33

 snow, 6-120

 sources, 6-104

Design procedure

 examples, 7-44, 7-51, 7-68

 introduction, 7-36

 path performance, 7-37

Distrometer, 2-10

Dispersion, phase and amplitude, 5-39

Diversity

 frequency, 7-79, 7-119

 measures of performance, 7-80

 orbit, 7-79, 7-84, 7-107

- measurements, 7-109
- path, see site
- signal 7-111
- site, 7-79, 7-86
 - definition, 7-80
 - design factors, 7-88
 - empirical models, 7-93, 7-95, 7-102, 7-107
 - experiments, 7-86
- space, 7-83
- Diversity advantage, 7-81
- Diversity improvement, 7-80
- Diversity gain
 - analytic model, 7-102
 - definition, 7-80
 - empirical model, 7-93
 - empirical model extension, 7-95
 - relative, 7-107
- Drop size distribution, 2-7
- DSCS III satellite, 7-30
- Dust attenuation, 6-73
- Dutton-Dougherty rain attenuation model, 3-2, 3-12

-E-

- ECS satellite, 5-3, 5-4
- Effective path length
 - attenuation model comparisons, 3-70
 - definition, 3-63
 - frequency dependence, 3-64
- Elevation angle scaling
 - depolarization, 6-113
 - rain attenuation, 6-48
- Elliptical polarization, 4-11
- ETS-II** satellite, 5-3, 5-4, 5-19, 5-24, 5-35
- European Broadcasting Union, 7-32

-F-

- Fade
 - distribution function, 6-95
 - mitigation, 7-78
 - simultaneous probabilities, 7-121
 - temporal distribution, 5-28
- Fade duration, 5-32, 6-50
 - annual distribution, 5-35, 6-56
 - daily distribution, 6-56
 - versus frequency of occurrence, 6-50
- Federal Communications Commission (FCC), 6-2
- FLTSATCOM** satellite, 7-30
- Fluctuations
 - amplitude, 6-76, 6-101
 - antenna aperature effects, 6-75
 - computation of
 - amplitude, 6-101

- angle-of-arrival, 6-103
 - gain reduction, 6-103
 - RMS phase delay, 6-103
- distribution function, 6-95
- . example, **6-101**
- gain degradation, 6-98
- overview of amplitude, 6-76
- phase, 6-90
- phase delay, 6-90
- phase ripple, **6-92**
- phase ripple gain degradation, 6-94
- power spectral density of amplitude, 6-82
- variance of signal amplitude, 6-76

Fog

- attenuation, 6-71
- attenuation prediction model, 6-72
- visibility
- water content, 6-71

Forward error correction (**FEC**), 7-28, 7-118

- adaptive, **7-79, 7-117**

Free space path loss, 7-52

Frequency bands, 6-2

Frequency diversity, 7-79, 7-119

Frequency reuse, 4-1, 5-36

Frequency scaling

- for polarization, 6-111
- for rain attenuation, 5-25, 6-47

-G-

Gain degradation, 6-82

- design information, 6-95
- domains, 6-98
- sample computation, 6-101

Gaseous attenuation

- elevation angle **dependence**, 6-12
- estimation procedure, 6-12
- frequency dependence, 6-7
- ground station altitude dependence, 6-8
- prediction, 6-6
- sample calculation, 6-16
- sources, 6-6
- standard deviation, 6-9
- surface temperature dependence, 6-12
- water vapor dependence, 6-8

Global rain attenuation model, 1-7, 3-2, 3-17, 6-23

- sample calculation, 6-29

-H-

Hourly Precipitation Data Report, 2-16

Hydrometers, 4-4

-I-

Ice, meteorological presence, 4-47
Ice depolarization (**see:** Depolarization, ice **crystal**)
INTELSAT VI satellite, 7-19, 7-29
Intense rain events
 annual and daily distributions, 6-56
Interference, 6-75
International Radio Consultative Committee: **see** **CCIR**
International Telecommunications Union (**ITU**), 6-2
Ionospheric effects, 6-5
Isolation, 4-4, 4-17
Isotherm, 0°C, 2-4, 3-26, 3-38
ITALSAT satellite, 7-33

-J-

Joss drop size distributions, 2-7

-K-

Laws and Parsons drop size distribution, 2-7
Lin rain attenuation model, 3-2, 3-54
Local **climatological** Data Report, 2-17
Low-angle fading, 6-85
 selected experimental results, 6-85
Low-angle scintillation, 6-82

-M-

Marshall-Palmer drop size distribution, 2-7
Model,
 CCIR, rain attenuation, 3-2, 3-44, 6-32
 CCIR, depolarization, 4-36, 5-33
 Dutton-Dougherty, 3-2, 3-12
 Global, 1-7, 3-2, 3-17, 6-23
 ice depolarization, 4-49
 Lin, 3-2, 3-54
 piecewise uniform, 3-59
 rain rate, 3-1
 rain depolarization, 4-23
 Rice-Holmberg, 3-2, 3-5
 SAM (Simple Attenuation Model), 3-2, 3-58
 two-component, 3-2, 3-39
Multipath depolarization, 6-120

-N-

National Climatic Data Center, 2-16
Noise (see also: Sky noise)
 cloud, 6-64
 sky, 1-4, 6-130
 temperature, 1-4
 uplink, 6-143
Non-ideal antenna, 4-15

-O-

OLYMPUS-1 satellite, 7-31, 7-34

- On-board processing, 7-20, 7-25, 7-34
- Orbit diversity, 7-79, 7-84, 7-107
 - measurements, 7-109
- OTS satellite, 5-3, 5-4, 5-18, 5-20
- Outage
 - duration, 7-8
 - period, 3-4
 - time 7-49
- Oxygen absorption, 1-3

- P-
- Partial pressure, saturated, 6-16
- Path diversity (see: Site diversity)
- Performance criteria, 7-7, 7-15
 - analog transmission, 7-12
 - digital transmission, 7-9
 - examples, 7-44, 7-53, 7-68
- Phase dispersion data, 5-39
- Phase fluctuations, 6-90, 6-103, 6-129, 6-131
- Piecewise uniform rain rate model, 3-59
- Polarization isolation, 4-2
- Polarization mismatch factor, **4-10**
- Polarization states, 4-7
- Power budget equation, 7-53
- Power control, 7-79, 7-112
 - downlink, 7-115
 - uplink**, 7-114
- Power spectral density, 6-82
- Prediction
 - amplitude fluctuations, 6-76
 - angle of arrival, 6-94
 - depolarization, 6-104, 6-122
 - CCIR approximation for rain, 6-106
 - CCIR factor for ice, 6-119
 - fog, 6-72
 - gaseous attenuation, 6-6, 6-11
 - gain degradation, 6-82, 6-103
 - introduction, 6-1
 - phase delay, 6-90
 - power spectral density, 6-82
 - rain attenuation, 6-20
 - CCIR** model, 6-32
 - Global model, 6-23
- Propagation beacons
 - ACTS, 7-26
 - Italsat**, 7-33
 - Olympus**, 7-32
 - summary table, 5-3
- Propagation data, 5-1
 - 11.5 - 11.7 GHz, 5-8
 - 15 - 16 GHz, 5-18
 - 19 - 20 GHz, 5-22

- 28 - 35 GHz, 5-22
- format, 5-5
- phase and amplitude dispersion, 5-39
- satellites used, 5-4
- summaries, 5-1
- temporal fade distribution, 5-28

-R-

Rain

- convective, 2-2
- debris, 3-42
- depolarization (see: Depolarization, rain)
- gauges, 2-23
- gauge integration time, 2-31
- spatial distribution, 2-2
- specific attenuation
- stratiform, 2-2
- volume cell, 3-41
- Rain attenuation, 1-6, 3-1
 - measurements (see: Propagation data)
 - models summary, 3-2
 - model comparisons, 3-61
 - statistics: see Attenuation statistics
 - prediction: see Prediction, rain attenuation
- Rain fade mitigation, 7-78
- Rain rate
 - climate regions
 - CCIR**, 3-45, 6-38
 - Global, 3-21, 6-24
 - cumulative distribution, 3-3, 6-26, 6-34
 - estimation from rain gauge records, 2-25, 2-28
 - long term distributions, 2-3
 - measurement, 2-23
 - models**, 3-2
 - path averaged, 3-29, 3-53, 3-55, 3-59
 - point, 3-1, 3-15, 3-18
 - short term distributions, 2-4
 - statistics, 2-1, 3-3
 - time variation, 2-25, 3-4, 5-28, 5-32
- Rainfall data, sources and types
 - Canada, 2-26
 - U.S., 2-13
 - worldwide, 2-28
- Rate of change of attenuation, 6-56
- Rate reduction, 7-80, 7-112
- Rayleigh scattering, 2-7
- Reflectivity factor, 2-4, 6-122
- Relative humidity, 6-16
- Resource sharing, 7-78
- Rice-Holmberg** rain rate model, 3-2, 3-5

-S-

SAM (Simple Attenuation Model), 3-2, 3-58

Sand attenuation, 6-73

Satellites

- ACTS, 7-18, 7-24, 7-78, 7-117
- ATDRSS, 7-35
- ATS-5, 5-21
- ATS-6, 4-40, 5-3, 5-4, 5-22
- BS, 5-3, 5-4
- COMSTAR, 4-40, 5-4, 5-22, 5-28, 5-29, 5-36, 5-39
- CS, 5-3, 5-4, 5-24
- CTS, 4-40, 5-4, 5-8
- DSCS III, 7-30
- ECS, 5-3, 5-4
- ETS-II, 5-3, 5-4, 5-19, 5-24, 5-35
- FLTSATCOM, 7-30
- INTELSAT-VI, 7-19, 7-29
- ITALSAT, 7-33
- OTS, 5-3, 5-4, 5-18, 5-20
- SIRIO, 4-40, 5-3, 5-4, 5-18, 5-19, 5-20

Saturated partial pressure, 6-16

Scintillation

- amplitude, 6-76, 6-101
- distribution function, 6-95
- phase, 6-90, 6-103

Signal diversity, 7-111

SIRIO satellite, 4-40, 5-3, 5-4, 5-18, 5-19, 5-20

Site diversity

- analytical model, 7-102, 7-107
- baseline orientation, 7-90
- definition, 7-80
- design factors, 7-88
- elevation angle, 7-90
- empirical model, 7-93
- experiments summary, 7-86
- extended empirical model, 7-95
- frequency dependence, 7-91
- interstation link, 7-92
- local climatology, 7-92
- multiple earth terminals, 7-93
- path azimuth angle, 7-90
- rain cell anisotropy, 7-91
- separation distance, 7-88
- switching rates, 7-92

Sky noise, 1-4, 6-130

- clear-air, 6-131
- clouds, 6-139
- computation of multiple contributors, 6-140
- dust, 6-139
- extraterrestrial sources, 6-140
- fog, 6-139
- lunar, 6-142

- radio stars, 6-142
- rain, 1-6, 6-136
- sample calculations, 6-136
- sand, 6-139
- solar, 6-140
- uplink, 6-143
- Sky noise temperature, 1-6
- Space diversity, 7-83
- Specific attenuation
 - dry air, 6-13
 - rain, 2-7, 2-11
 - frequency dependence, **2-11**
 - rain rate dependence, 2-11, 2-14
 - regression values, 2-12, 2-14, 6-40
 - water droplets, 6-62
 - water vapor, 6-62
- Storm Data Report, 2-17
- SS/TDMA 7-17, 7-32
- System design
 - availability allocation, 7-37, 7-73
 - clear-air absorption, 7-63
 - composite carrier-to-noise ratio, 7-48, 7-71
 - depolarization analysis, 7-58
 - initial phase, 7-43
 - overview of procedure, 7-1
 - phases, 7-40
 - power budget, 7-50
 - sample calculation, 7-64
 - process, 7-3, 7-41
 - propagation analysis, 7-42, 7-55, 7-63
 - rain margin, 7-55
 - synthesis phase, 7-46
 - sample calculation, 7-52
- System performance criteria
 - analog, 7-12
 - bit error rate, 7-9
 - CCIR**, 7-9
 - DCA, 7-9
 - digital, 7-9
 - examples, 7-43
 - overview summary, 7-7

-T-

- TDMA** (time division multiple access), 6-5, 7-17, 7-21, 7-117
 - satellite switched (SS), 7-17, 7-32
- Telecommunications services, 6-4
- Throughput, 7-11
- Transmission coefficient, 4-25
- Tropospheric delays, 6-5
- Two-component rain attenuation model, 3-2, 3-39

-U-

- Uplink** Noise, 6-143

-V-

Volume cell rainfall, 3-41

VSAT, 7-23

-W-

Wave antenna interaction, 4-8

Water vapor

and relative humidity, **6-16**

definition, 6-16

density, 6-14

specific attenuation, 6-13

Worst month statistics, 6-59

-X-

XPD (see: Crosspolarization discrimination)

XPI (see: Crosspolarization isolation)

-Z-

Zero degree isotherm, 2-4, 3-26, 3-38, 6-23

1. Report No. NASA RP-1082(04)		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle Propagation Effects Handbook for Satellite Systems Design - A Summary of Propagation Impairments on 10 to 100 GHz Satellite Links With Techniques for System Design				5. Report Date February 1989	
				6. Performing Organization Code	
7. Author(s) Louis J. Ippolito				8. Performing Organization Report No.	
				10. Work Unit No.	
9. Performing Organization Name and Address Westinghouse Electric Corporation Friendship Site Box 1897 Baltimore, MD 21203				11. Contractor Grant No. NAS7-100;958178(JPL)	
				13. Type of Report and Period Covered Reference Publication (Fourth Edition)	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, DC 20546 Office of Space Science and Applications				14. Sponsoring Agency Code	
15. Supplementary Notes					
16. Abstract The NASA Propagation Effects Handbook for Satellite Systems Design provides a systematic compilation of the major propagation effects experienced on space-Earth paths in the 10 to 100 GHz frequency band region. It provides both a detailed description of the propagation phenomena and a summary of the impact of the effect on communications system design and performance. Chapters II through V describe the propagation effects, prediction models, and available experimental data bases. In Chapter VI, design techniques and prediction methods available for evaluating propagation effects on space-Earth communications systems are presented. Chapter VII addresses the system design process and how the effects of propagation on system design and performance should be considered and how they can be mitigated. Examples of operational and planned K_u , K_a , and EHF satellite communications systems are given.					
17. Key Words (Suggested by Author(s)) Microwave Propagation, Rain Attenuation, Satellite Communications Systems, K_u , K_a , EHF Propagation, Radio Noise				18. Distribution Statement Unclassified - Unlimited Subject Category 32	
19. Security Class. (of this report) Unclassified		20. Security Class. (of this page) Unclassified		21. No. of pages 536	22. Price A23